


262M

Double-Coated PET Film Tape



Liner: 60# Silicone-Coated Densified Kraft

Liner Side Adhesive: Rubber (1915)

Backing/Carrier: 0.5 mil PET Film

Air Side Adhesive: Rubber (1915)

Applications

 Bonding and laminating to a variety of plastics metals, and papers

- Bonding and laminating to a variety of plastics, Laminating to cork, felt, abrasives, and more
 - Splicing and general purpose holding

Features Benefits

Rubber Adhesive	 Excellent quick stick to difficult surfaces 	
	 Moderate shear strength 	
Polyester Film Carrier	 Support for aid in processing and application 	
	 Conformable 	
• 60# Kraft Liner	Easily die-cut	

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Overall Thickness (w/liner)	6.5 mils	0.165 mm	PSTC 133
Adhesive Thickness (Air Side)	1.25 mils	0.032 mm	PSTC 133
Carrier Thickness	0.5 mils	0.013 mm	PSTC 133
Adhesive Thickness (Liner Side)	1.25 mils	0.032 mm	PSTC 133
Liner Thickness	3.5 mils	0.089 mm	PSTC 133
Adhesion to Steel (Air Side)	110 oz/in	12.03 N/cm	PSTC 101 Mod - 1 mil PET
Adhesion to Steel (Liner Side)	110 oz/in	12.03 N/cm	PSTC 101 Mod - 1 mil PET
Adhesion to Steel (Air Side)	128 oz/in	14.00 N/cm	PSTC 101 Mod - 2 mil Alu Foil
Adhesion to Steel (Liner Side)	128 oz/in	14.00 N/cm	PSTC 101 Mod - 2 mil Alu Foil
Shear Strength	>7 Days		PSTC 107 Mod
Laminating Temperature	68 to 100 °F	20 to 38 °C	
Service Temperature	30 to 150 °F	-1 to 66 °C	

Recommended Storage Conditions: 40-60% Humidity, 60 °F - 80 °F

Standard Shelf Life: 12 months from date of shipment

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

