


33M8H

Double-Coated Tape



Liner: 80lb semi-bleached super-calendered

kraft, silicone release coated on both

sides

Liner Side Adhesive: Acrylic (1607)

Backing/Carrier: 0.5 mil polyester film

Air Side Adhesive: Acrylic (1607)

Applications

Gasket assembly

Mounting nameplates, decals, and plastic trim

 Laminating paper, felt, sponge rubber, foam, and plastics

Benefits

Features

•	Polyester Film Carrier	Support for aid in processing and applicationConformable
•	Acrylic Adhesive	 Excellent anchorage to foams and plastics Excellent performance over a wide temperature range Humidity and plasticizer migration resistant
•	80lb Semi-bleached SC Kraft Liner	 Ideal for kiss cutting applications

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness w/liner	9.0 mils	0.229 mm	PSTC 133
Adhesive Thickness (Air Side)	1.9 mils	0.048 mm	PSTC 133
Adhesive Thickness (Liner Side)	1.9 mils	0.048 mm	PSTC 133
Carrier Thickness	0.5 mils	0.013 mm	PSTC 133
Liner Thickness	4.7 mils	0.119 mm	PSTC 133
Adhesion to Steel (Air Side)	88 oz/in	9.63 N/cm	PSTC 101 Mod
Adhesion to Steel (Liner Side)	95 oz/in	10.39 N/cm	PSTC 101 Mod
Shear Strength (Air Side)	>24 hours		PSTC 107
Shear Strength (Liner Side)	>24 hours		PSTC 107
Laminating Temperature	50 to 150 °F	10 to 65 °C	
Maximum Continuous Use	200 °F	93 °C	
Intermittent Use	250 °F	121 °C	

Recommended Storage Conditions: 40-60% Humidity, 60 °F - 80 °F

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

