


3000-47

Transfer Adhesive



Adhesive: Acrylic (I607)

Liner: 76lb white polycoated kraft liner

Applications

- Laminating paper, felt, sponge rubber, foam, and plastic
- Mounting nameplates, plastic trim, decals
- Gasket assembly
- Weather stripping

Features

- Acrylic Adhesive
- 76lb Release Liner

Benefits

- Good humidity and stress resistance
- Aggressive bond
- Adheres well to foams and plastics including PE, TPO, ABS, and PP
- Excellent plasticizer migration resistance
- Dimensionally stable
- Moisture resistant

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness w/liner	11.0 mils	0.279 mm	PSTC 133
Adhesive Thickness	4.0 mils	0.102 mm	PSTC 133
Liner Thickness	6.0 mils	0.152 mm	PSTC 133
Adhesion to Steel	130 oz/in	14.22 N/cm	PSTC 101 Mod
Shear Strength	>24 hours		PSTC 107
Laminating Temperature	50 to 150 °F	10 to 65 °C	
Maximum Continuous Use	200 °F	93 °C	
Intermittent Use	250 °F	121 °C	

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.