


# POLYKEN<sup>®</sup> 2108G

## Single-Coated Foam Tape



- Backing:** 1/16" white, crosslinked polyethylene foam
- Adhesive:** Non-irritating acrylic (M111)
- Liner:** 2 mil polyester film, silicone coated on one side

### Applications

- Electrodes: ECG, EKG, TENS
- AED defibrillator pads
- Medical device mounting
- Transdermal delivery system

### Features

- Polyethylene Foam Backing
- Acrylic Adhesive
- Polyester Film Liner

### Benefits

- Soft and flexible for maximum patient comfort
- Conformable and easily adapts to medical devices and body contours
- Strong adhesion to surfaces
- Excellent lay flat and dimensional stability
- Easily die-cut

### Typical Test Values

	Standard UOM	Metric UOM	Test Method
<b>Total Thickness w/liner</b>	65.3 mils	1.659 mm	PSTC 133
<b>Adhesive Thickness</b>	0.8 mils	0.020 mm	PSTC 133
<b>Carrier Thickness</b>	62.5 mils	1.588 mm	PSTC 133
<b>Liner Thickness</b>	2.0 mils	0.051 mm	PSTC 133
<b>Adhesion to Steel</b>	82 oz/in	8.97 N/cm	PSTC 101 Mod

### Product Safety

The base adhesives in this medical product have been tested in accordance with ISO 10993 and found to be non-cytotoxic, and non-irritating.

Recommended Storage Conditions: 40-60% Humidity, 60 °F - 80 °F

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.